

# Converting a microPod from wiTECH 2.0 to Enhanced DRB III Emulator

300 Emil Ghiurau Mon, Jul 2, 2018 [wiTECH 2 Public Articles](#) 3899

## DESCRIPTION

As of **April 28, 2016**, due to new registration requirements, a microPod device will no longer be compatible with wiTECH 1.0 after it is registered with wiTECH 2.0.

Once a device is registered for wiTECH 2.0, it can no longer be converted to be used with wiTECH 1.0 again. We highly recommend assigning a dedicated microPod device to be used with wiTECH 1.0 when needed.



### wiTECH 2.0 Device Setup & Configuration:

Due to new registration requirements, a microPOD device will no longer be compatible with wiTECH 1.0 after it is registered with wiTECH 2.0.

Once a device is registered for wiTECH 2.0, it can no longer be converted to be used with wiTECH 1.0 again. We highly recommend assigning a dedicated microPOD device to be used with wiTECH 1.0 when needed.

To setup your microPOD device with wiTECH 2.0, click "Continue".

To configure the wireless settings on a microPOD device to use with wiTECH 2.0, click "Wireless Configuration".

Continue

Wireless Configuration

microPod II devices are a cost effective diagnostic solution for your dealership. We strongly recommend that your dealership purchases an adequate number of microPods for your technicians. To purchase additional microPods, you can login to [www.witechsystem.com](http://www.witechsystem.com) and go to Order Products >Begin Shopping>wiTECH Products>wiTECH Diagnostic Extender microPod II.

**Reminder: FCA highly recommends that every dealership has at least one microPod dedicated for use with Enhanced DRB III Emulator.**

Online URL: <https://kb.l.fcaitech.com/article/converting-a-micropod-from-witech-2-0-to-enhanced-drb-iii-emulator-300.html>